# PLAT


## PL306035PR4030DW



### PLAT G3 600X600 3200 WW PRIS IP40 DA WH

#### **Description:**

Recessed or suspended luminaire model PLAT G3, LAMP brand. Made of matt white steel with prismatic polycarbonate diffuser. Model with MID-POWER LED, 3000K colour temperature and CRI 80. Control DALI gear included. Glare rating <19 (for 4h, 8h 70/50/20). With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK06. Insulation class II. Photobiological safety group 0. Lifetime: 70.000h L80 B10



Finish:Matte Traffic white RAL 9016Dimensions:596 x 596 x 14 mm

Weight: 3.900 g

Installation: Recessed

#### **TECHNICAL SPECIFICATIONS:**

Light output:	3.395 lm	°K :	3000
Plum:	31W	CRI :	80
Efficacy:	109,5 lm/w	MacAdam:	3
UGR:	19	Power Supply:	220-240V 50/60Hz
Туре:	MID POWER LED	Gear:	Adjustable DALI
LED Lifetime:	70.000 L80 B10 (Ta=25⁰C)		
Power:	28W		

#### Light output tolerance +/- 10%



Worktitude for light

# PLAT

PL306035PR4030DW

PLAT G3 600X600 3200 WW PRIS IP40 DA WH



PL306035PR4030NW	180°	alpha = 95,1°	H (m)	D (m)	Emax	Emed
η = 100% Imax = 417 cd/klm			1	2,19	1398	653
UTE: 1,00D	90° 90°		2	4,37	350	163
CIE: 59 88 97 100 100			3	6,56	155	73
			1	8,75	87	41
	0°		4	0,75	07	41

Worktitude for light

# PLAT



## ACCESORIES :

## Assembly



Product code: PLREFR060 Description: PLAT ACC. FRAME REC 600X600MM WH.



Product code: PLSFFR060 Description: PLAT ACC. FRAME SUR 600X600MM WH.

# ACCESORIES : Suspension



Product code: PLSUWI1500 Description: PLAT G3 ACC. SUSP KIT







LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es