#### **Product datasheet**

#### **PLAT**

#### PL312035OP4030DW



#### PLAT G3 1200X300 3400 WW OPAL IP40 DA WH

#### Description:

Recessed or suspended luminaire model PLAT G3, LAMP brand. Made of matt white steel with opal polycarbonate diffuser. Model with MID-POWER LED, 3000K colour temperature and CRI 80. Control DALI gear included. With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK06. Insulation class II. Photobiological safety group 0. Lifetime: 70.000h L80 B10.



Finish: Matte Traffic white RAL 9016

1.196 x 296 x 14 mm Dimensions: Weight: 3.900 g

Installation: Recessed

#### **TECHNICAL SPECIFICATIONS:**

Light output: 3.607 Im °K: 3000 Plum: 32W CRI: 80 Efficacy: 116,4 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

30W Power:

### Light output tolerance +/- 10%



































+34937366800

## **PLAT**







## PLAT G3 1200X300 3400 WW OPAL IP40 DA WH

#### **PHOTOMETRIC DATA:**

PL312035OP4030NW  $\eta$  = 100% lmax = 345 cd/klm UTE: 1,00E

CIE: 46 78 96 100 100





alpha = 114,1°	H (m)	D (m)	Emax	Emed
	1	3,08	1242	360
	2	6,17	311	90
	3	9,25	138	40
	4	12,34	78	23

## **Product datasheet**

## **PLAT**



## ACCESORIES:

## **Assembly**



Product code: Description:

PLREFR120 PLAT ACC. FRAME REC 1200X300MM WH.



Product code:

Description: PLSFFR120

PLAT ACC. FRAME SUR 1200X300MM WH.

## **ACCESORIES:**

## Suspension



Product code:

Description:

PLSUWI1500 PLAT G3 ACC. SUSP KIT

# **PLAT**





