PLAT

PL312035OP4030NW



PLAT G3 1200X300 3400 WW OPAL IP40 WH

Description:

Recessed or suspended luminaire model PLAT G3, LAMP brand. Made of matt white steel with opal polycarbonate diffuser. Model with MID-POWER LED, 3000K colour temperature and CRI 80. Control gear included. With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK06. Insulation class II. Photobiological safety group 0. Lifetime: 60.000h L80 B10.



Finish:Matte Traffic white RAL 9016Dimensions:1.196 x 296 x 14 mm

Weight: 3.900 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	3.607 lm	⁰K :	3000		
Plum:	32W	CRI :	80		
Efficacy:	116,4 lm/w	MacAdam:	3		
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz		
LED Lifetime:	70.000 L80 B10 (Ta=25°C)	Gear:	Electronic		
Power:	30W				

Light output tolerance +/- 10%



Worktitude for light

PLAT

PL312035OP4030NW

PLAT G3 1200X300 3400 WW OPAL IP40 WH



PHOTOMETRIC DATA :

PL312035OP4030NW	180°	alpha = 114,1°	H (m)	D (m)	Emax	Emed
η = 100%			1	3,08	1242	360
Imax = 345 cd/klm						
UTE: 1,00E	90° 90°		2	6,17	311	90
CIE: 46 78 96 100 100						
			3	9,25	138	40
	Q°		4	12,34	78	23

PLAT



ACCESORIES :

Assembly



Product code:Description:PLREFR120PLAT ACC. FRAM

PLAT ACC. FRAME REC 1200X300MM WH.



H. PLSFFR120

Description: PLAT ACC. FRAME SUR 1200X300MM WH.

ACCESORIES : Suspension



Product code: PLSUWI1500 Description: PLAT G3 ACC. SUSP KIT







LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es