Product datasheet

PLAT


PL312035PR4030DW



PLAT G3 1200X300 3200 WW PRIS IP40 DA WH

Description:

Recessed or suspended luminaire model PLAT G3, LAMP brand. Made of matt white steel with prismatic polycarbonate diffuser. Model with MID-POWER LED, 3000Kcolour temperature and CRI 80. Control DALI gear included. Glare rating <19 (for 4h, 8h 70/50/20). With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK06. Insulation class II. Photobiological safety group 0. Lifetime: 70.000h L80 B10



Finish: Matte Traffic white RAL 9016

1.196 x 296 x 14 mm Dimensions: Weight: 3.900 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.395 lm °K: 3000 Plum: 32W CRI: 80 Efficacy: 109,5 lm/w 3 MacAdam:

UGR: 19

Type: MID POWER LED

LED Lifetime: 70.000 L80 B10 (Ta=25°C)

Power: 30W

Light output tolerance +/- 10%















Power Supply:

Gear:

220-240V 50/60Hz

Adjustable DALI













PLAT






PLAT G3 1200X300 3200 WW PRIS IP40 DA WH

PHOTOMETRIC DATA:

PL312035PR4030NW η = 100% Imax = 417 cd/klm UTE: 1,00D

CIE: 59 88 97 100 100





alpha = 95,1°	H (m)	D (
	1	2
	2	4
	3	6
	4	8

H (m)	D (m)	Emax	Emed
1	2,19	1398	653
2	4,37	350	163
3	6,56	155	73
4	8,75	87	41

Product datasheet

PLAT



ACCESORIES:

Assembly



Product code: Description:

PLREFR120 PLAT ACC. FRAME REC 1200X300MM WH.



Product code:

Description: PLSFFR120

PLAT ACC. FRAME SUR 1200X300MM WH.

ACCESORIES:

Suspension



Product code:

Description:

PLSUWI1500 PLAT G3 ACC. SUSP KIT

PLAT





