Product datasheet

PLAT


PL312035PR40840DW



PLAT G3 1200X300 3400 840 PRIS IP40 DA W

Description:

Recessed or suspended luminaire model PLAT G3, LAMP brand. Made of matt white steel with prismatic polycarbonate diffuser. Model with MID-POWER LED, 4000K colour temperature and CRI 80. Control DALI gear included.Glare rating <19 (for 4h, 8h 70/50/20). With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK06. Insulation class II. Photobiological safety group 0. Lifetime: 70.000h L80 B10.



Finish: Matte Traffic white RAL 9016

1.196 x 296 x 14 mm Dimensions: Weight: 3.900 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.607 Im °K: 4000 Plum: 33,6W CRI: 80 Efficacy: 116,4 lm/w 3 MacAdam:

UGR: <19 Power Supply: 220-240V 50/60Hz Type: MID POWER LED Gear: Adjustable DALI

LED Lifetime: 70.000 L80 B10 (Ta=25°C)

30W Power:

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:
























PLAT










PHOTOMETRIC DATA:

PL312035PR40840DW η = 101% lmax = 434 cd/klmUTE: 1,00D + 0,01T CIE: 60 87 97 99 101







Product datasheet

PLAT



ACCESORIES:

Assembly



Product code: Description:

PLREFR120 PLAT ACC. FRAME REC 1200X300MM WH.



Product code:

Description: PLSFFR120

PLAT ACC. FRAME SUR 1200X300MM WH.

ACCESORIES:

Suspension



Product code:

Description:

PLSUWI1500 PLAT G3 ACC. SUSP KIT