Product datasheet

PLAT

PL312040PR4035DW

PLAT G3 1200X300 4200 835 PRIS IP40 DA W

Description:

Recessed or suspended luminaire model PLAT G3, LAMP brand. Made of matt white steel with prismatic polycarbonate diffuser. Model with MID-POWER LED, 3500K colour temperature and CRI 80. Control DALI gear included. Glare rating <19 (for 4h, 8h 70/50/20). With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK06. Insulation class II. Photobiological safety group 0. Lifetime: 70.000h L80 B10



Finish: Matte Traffic white RAL 9016

1.196 x 296 x 14 mm Dimensions: Weight: 3.900 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.500 lm °K: 3500 Plum: 30W CRI: 80 Efficacy: 116,7 lm/w 3 MacAdam:

UGR:

Type: MID POWER SAMSUNG Gear: Adjustable DALI

LED Lifetime: 70.000 L80 B10 (Ta=25°C)

Power: 28W

Light output tolerance +/- 10%

































CUSTOM MADE OPTIONS:



















Power Supply:

220-240V 50/60Hz



PLAT








PLAT G3 1200X300 4200 835 PRIS IP40 DA W

PHOTOMETRIC DATA:

PL312040PR4035DW
η = 101%
Imax = 434 cd/klm
UTE: 1,00D + 0,01T
CIE: 60 87 97 99 101







Product datasheet

PLAT



ACCESORIES:

Assembly



Product code:

PLREFR120

Description:

PLAT ACC. FRAME REC 1200X300MM WH.



Product code:

PLSFFR120

Description:

PLAT ACC. FRAME SUR 1200X300MM WH.



Product code:

Description:

PLXSFCL PLAT X2 ACC 4/6 STEEL MOUNTING CLIPS SUR

ACCESORIES:

Suspension



Product code:

Description:

PLSUWI1500 PLAT X2 ACC. SUSP KIT