Product datasheet

PLAT




PLX206035OP4030NW



PLAT X2 600X600 3600 WW OPAL IP40 WH

Description:

Recessed or suspended luminaire model PLAT X2, LAMP brand. Made of matt white steel with opal polycarbonate diffuser (PMMA). Model with MID-POWER LED, 3000K colour temperature and CRI 80. Control gear included. With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK03. Insulation class II. Photobiological safety group 0. Lifetime: 60.000h L80 B10.



Finish: Matte Traffic white RAL 9016

595 x 595 x 12,5 mm Dimensions: Weight: 2.800 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.500 lm °K: 3000 Plum: 30,5W CRI: 80 Efficacy: 114,8 lm/w 3 MacAdam:

UGR: 22

LED Lifetime:

Power Supply: 220-240V 50/60Hz Type: MID POWER Gear: Electronic

Power: 26W

Light output tolerance +/- 10%























60.000 L80 B10







CUSTOM MADE OPTIONS:





















PLAT





PLAT X2 600X600 3600 WW OPAL IP40 WH

PHOTOMETRIC DATA:

PLX206035OP4030NW η = 100% Imax = 341 cd/klm UTE: 1,00E

CIE: 46 78 95 100 100

