Product datasheet

PLAT




PLX206035OP4040DW



PLAT X2 600X600 3600 NW OPAL IP40 DA WH

Description:

Recessed or suspended luminaire model PLAT X2, LAMP brand. Made of matt white steel with opal polycarbonate diffuser (PMMA). Model with MID-POWER LED, 4000K colour temperature and CRI 80. Control DALI gear included. With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK03. Insulation class II. Photobiological safety group 0. Lifetime: 60.000h L80 B10.



Finish: Matte Traffic white RAL 9016

595 x 595 x 12,5 mm Dimensions: Weight: 2.800 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.600 lm °K: 4000 Plum: 30,5W CRI: 80 Efficacy: 118 lm/w 3 MacAdam:

UGR: 22

Type: MID POWER Gear: Adjustable DALI

LED Lifetime: 60.000 L80 B10

Power: 26W































CUSTOM MADE OPTIONS:



















Power Supply:

220-240V 50/60Hz







PLAT X2 600X600 3600 NW OPAL IP40 DA WH

PHOTOMETRIC DATA:

PLX206035OP4040NW η = 100% Imax = 341 cd/klm UTE: 1,00E

CIE: 46 78 95 100 100

