Product datasheet

PLAT




PLX206035OP5430NW



PLAT X2 600X600 3600 WW OPAL IP54 WH

Description:

Recessed or suspended luminaire model PLAT X2 600X600 3600 WW OPAL IP54 WH, LAMP brand. Made of matt white steel with opal polycarbonate diffuser. Model with MID-POWER LED, warm white colour temperature and control gear included. 60.000L80B10. With a protection rating of IP54 (non-recessed part) and IP20 (recessed part), IK06. Insulation class II. Photobiological safety group 0.



Finish: Matte Traffic white RAL 9016

595 x 595 x 12,5 mm Dimensions: Weight: 2.800 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.500 lm °K: 3000 Plum: 30,5W CRI: 80 Efficacy: 114,8 lm/w 3 MacAdam:

UGR:

Type: MID POWER Gear: Electronic

LED Lifetime: 60.000 L80 B10

Power: 26W



























CUSTOM MADE OPTIONS:



















Power Supply:

220-240V 50/60Hz







PLAT X2 600X600 3600 WW OPAL IP54 WH

PHOTOMETRIC DATA:

PLX206035OP5430NW η = 100% Imax = 341 cd/klm UTE: 1,00E

CIE: 46 78 95 100 100

