Product datasheet

PLAT




PLX206035PR4030NW



PLAT X2 600X600 3400 WW PRIS IP40 WH

Description:

Recessed or suspended luminaire model PLAT X2, LAMP brand. Made of matt white steel with prismatic polycarbonate diffuser (PMMA). Model with MID-POWER LED, 3000K colour temperature and CRI 80. Control gear included. With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK03. Insulation class II. Photobiological safety group 0. Lifetime: 60.000h L80 B10



Finish: Matte Traffic white RAL 9016

595 x 595 x 12,5 mm Dimensions: Weight: 2.800 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.325 lm °K: 3000 Plum: 30,5W CRI: 80 Efficacy: 109 lm/w 3 MacAdam:

UGR: 19

Type: MID POWER Gear: Electronic

Power: 26W

LED Lifetime:

Light output tolerance +/- 10%









60.000 L80 B10





















CUSTOM MADE OPTIONS:



















Power Supply:

220-240V 50/60Hz



PLAT





PLAT X2 600X600 3400 WW PRIS IP40 WH

PHOTOMETRIC DATA:

PLX206035PR4030NW η = 101% Imax = 451 cd/klm UTE: 1,01D + 0,01T CIE: 60 87 97 99 101

