Product datasheet

PLAT



PLX212030PR4030NW



PLAT X2 1200X300 3400 WW PRIS IP40 WH

Description:

Recessed or suspended luminaire model PLAT X2, LAMP brand. Made of matt white steel with prismatic polycarbonate diffuser (PMMA). Model with MID-POWER LED, 3000K colour temperature and CRI 80. Control gear included. Glare rating <19 (for 4h, 8h 70/50/20). With a protection rating of IP40 (non-recessed part) and IP20 (recessed part), IK03. Insulation class II. Photobiological safety group 0. Lifetime: 60.000h L80 B10.



Finish: Matte Traffic white RAL 9016

1.195 x 295 x 12,5 mm Dimensions: Weight: 3.900 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.210 lm °K: 3000 Plum: 31,5W CRI: 80 Efficacy: 101,9 lm/w 3 MacAdam:

UGR: 19

Type: MID POWER Gear: Electronic LED Lifetime:

Power: 27W

Light output tolerance +/- 10%









60.000 L80 B10





















CUSTOM MADE OPTIONS:



















Power Supply:

220-240V 50/60Hz



PLAT







PHOTOMETRIC DATA:

PLX212030PR4030NW η = 100% Imax = 529 cd/klm UTE: 1,00C + 0,00T CIE: 64 89 98 100 100





