
### **QBF41112MOPR840D**



### QUIET BAF FIL45 1120 2600 OP COM NW DALI

### Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET BAFFLE FIL45 1120 .Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, dø. LOW VOC and Low formaldehyde emissions. Luminaire model F41RE112MOPR840DW 4000K and CRI80. Electronic DALI gear included. IP43, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: 70.000 L80 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.



Installation: Suspended

### **TECHNICAL SPECIFICATIONS:**

Light output: 2.017 lm °K: 4000 Plum: 20,6W CRI: 80 Efficacy: 97,9 lm/w 3 MacAdam:

UGR: <16 Power Supply: 220-240V 50/60Hz Type: MID POWER LED Gear: Adjustable DALI

LED Lifetime: 70.000 L80 B10 (Ta=25°C)

17,9W Power:

# Light output tolerance +/- 10%



CLASE

















































# **QBF41112MOPR840D**

# QUIET BAF FIL45 1120 2600 OP COM NW DALI

### **PHOTOMETRIC DATA:**

F41RE112MOPR840NW  $\eta = 99\%$ Imax = 968 cd/klm UTE: 0,99A

CIE: 90 100 100 100 99

