


## **QBF41168MOPR840N**



## **QUIET BAF FIL45 1680 3900 OP COM NW**

## Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET BAFFLE FIL45 1680. Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, dø. LOW VOC and Low formaldehyde emissions. Luminaire model F41RE168MOPR840NW 4000K and CRI80. Electronic ON OFF gear included. IP43, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: 70.000 L80 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.



Installation: Suspended

## **TECHNICAL SPECIFICATIONS:**

Light output: 3.026 Im °K: 4000 Plum: 30,8W CRI: 80 Efficacy: 98,2 lm/w 3 MacAdam:

UGR:

Type: MID POWER LED

LED Lifetime: 70.000 L80 B10 (Ta=25°C)

26,9W Power:

# Light output tolerance +/- 10%



CLASE



































Data according to regulations 2019/2020/EU and 2019/2015/EU











Power Supply:

Gear:

220-240V 50/60Hz

Electronic





# QBF41168MOPR840N

# **QUIET BAF FIL45 1680 3900 OP COM NW**

## **PHOTOMETRIC DATA:**

F41RE168MOPR840NW  $\eta$  = 99% Imax = 968 cd/klm UTE: 0,99A

CIE: 90 100 100 100 99

