


QHOD10612WF830N



QUIET HEX OCULT 1x6 1200 WW WFL

Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET HEX OCULT 1x6.Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, dø. LOW VOC and Low formaldehyde emissions. Luminaire model OD1RE612WF830NBB 3000K and CRI80. Electronic ON OFF gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.



Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.098 lm °K: 3000 Plum: 14W CRI: 80 Efficacy: 78,4 lm/w 3 MacAdam:

UGR: <16

HIGH POWER LED

LED Lifetime: 50.000 L90 B10 (Ta=25°C)

12W Power:

Light output tolerance +/- 10%



Type:













CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU











Power Supply:

Gear:

220-240V 50/60Hz

Electronic





QHOD10612WF830N

QUIET HEX OCULT 1x6 1200 WW WFL

PHOTOMETRIC DATA:

OD1RE612WF830NBB η = 100% Imax = 1615 cd/klm UTE:

