# Worktitude for light


## QHOD11624MF840D



## QUIET HEX OCULT 2x6 2400 NW MFL DALI

## Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET HEX OCULT 2x6. Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, dø. LOW VOC and Low formaldehyde emissions. Luminaire model OD1RE612MF840DBB 4000K and CRI80. Electronic DALI gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.



Installation: Suspended

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.160 lm
 ⁰K:
 4000

 Plum:
 28W
 CRI:
 80

 Efficacy:
 77,1 lm/w
 MacAdam:
 3

**UGR**: <10

Type: HIGH POWER LED Gear: Adjustable DALI

**LED Lifetime:** 50.000 L90 B10 (Ta=25°C)

Power: 12W

# Light output tolerance +/- 10%















# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU











Power Supply:





100-240V 50/60Hz





# QHOD11624MF840D


# QUIET HEX OCULT 2x6 2400 NW MFL DALI

## **PHOTOMETRIC DATA:**

OD1RE612MF840NBB  $_{\eta}$  = 100%  $_{\rm Imax}$  = 4606 cd/klm UTE: CIE: 102 100 100 100 100







Data according to regulations 2019/2020/EU and 2019/2015/EU





