# Worktitude for light


#### QHOD11624MF840N



#### QUIET HEX OCULT 2x6 2400 NW MFL

#### Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET HEX OCULT 2x6. Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, dø. LOW VOC and Low formaldehyde emissions. Luminaire model OD1RE612MF840NBB 4000K and CRI80. Electronic ON OFF gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.



Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.160 lm
 ⁰K:
 4000

 Plum:
 28W
 CRI:
 80

 Efficacy:
 77,1 lm/w
 MacAdam:
 3

**UGR**: <10

Type: HIGH POWER LED

**LED Lifetime:** 50.000 L90 B10 (Ta=25°C)

Power: 12W

Light output tolerance +/- 10%

















### **CUSTOM MADE OPTIONS:**



















Power Supply:

Gear:





220-240V 50/60Hz

Electronic



## QHOD11624MF840N

## QUIET HEX OCULT 2x6 2400 NW MFL

#### **PHOTOMETRIC DATA:**

OD1RE612MF840NBB  $\eta$  = 100% lmax = 4606 cd/klmUTE: CIE: 102 100 100 100 100

