


QRK1120OP830N



QUIET RD KOMBIC 100 2000 WW OP

Description:


LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET RD KOMBIC 100 .Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, d0. LOW VOC and Low formaldehyde emissions. Luminaire model K11RD2040OP830NWW 3000K and CRI80. Electronic ON OFF gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L80 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.454 lm	°K :	3000
Plum:	13,4W	CRI :	80
Efficacy:	108,5 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	12W		

Light output tolerance +/- 10%




CUSTOM MADE OPTIONS:



QRK1120OP830N

QUIET RD KOMBIC 100 2000 WW OP

PHOTOMETRIC DATA :



Essential Colours



Trendy Colours



Prime Colours

