


QRK1120OP840D




QUIET RD KOMBIC 100 2000 NW OP DALI

Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET RD KOMBIC 100 .Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, d0. LOW VOC and Low formaldehyde emissions. Luminaire model K11RD2040OP840DWW 4000K and CRI80. Electronic DALI gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L80 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.

Installation: Suspended
TECHNICAL SPECIFICATIONS:


Light output:	1.541 lm	°K :	4000
Plum:	13,4W	CRI :	80
Efficacy:	115 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	12W		

Light output tolerance +/- 10%
**CUSTOM MADE OPTIONS:**

QRK11200P840D

QUIET RD KOMBIC 100 2000 NW OP DALI

PHOTOMETRIC DATA :



Essential Colours



Trendy Colours



Prime Colours

