


QRK2130WF840N



QUIET RD KOMBIC 150 2800 NW WFL

Description:


LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET RD KOMBIC 150 .Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, d0. LOW VOC and Low formaldehyde emissions. Luminaire model K21RD3040WF840NWW 4000K and CRI80. Electronic ON OFF gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L80 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.737 lm	°K :	4000
Plum:	19,1W	CRI :	80
Efficacy:	90,9 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	COB	Gear:	Electronic
LED Lifetime:	50.000 L70 B10 (Ta=25°C)		
Power:	17,6W		

Light output tolerance +/- 10%




CUSTOM MADE OPTIONS:



QRK2130WF840N

QUIET RD KOMBIC 150 2800 NW WFL

PHOTOMETRIC DATA :



Essential Colours



Trendy Colours



Prime Colours

