Worktitude for light


QROD12624WF830D



QUIET RECTANGLE OCULT 2x6 2400 WW WFL D

Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET RECTANGLE OCULT 2x6 .Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, dø. LOW VOC and Low formaldehyde emissions. Luminaire model OD1RE612WF830DBB 3000K and CRI80. Electronic DALI gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.



Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 2.160 lm
 ⁰K:
 3000

 Plum:
 28W
 CRI:
 80

 Efficacy:
 78,4 lm/w
 MacAdam:
 3

 UGR:
 <16</td>
 Power Supply:
 100-240V 50/60Hz

 Type:
 HIGH POWER LED
 Gear:
 Adjustable DALI

LED Lifetime: 50.000 L90 B10 (Ta=25°C)

Power: 12W

Light output tolerance +/- 10%















CUSTOM MADE OPTIONS:























QUIET RECTANGLE OCULT 2x6 2400 WW WFL D

PHOTOMETRIC DATA:

OD1RE612WF830NBB η = 100% Imax = 1615 cd/klm Imax UTE: CIE: 99 100 100 100 100

