Worktitude for light


QROD12936MF830D



QUIET RECTANGLE OCULT 2x9 3600 WW MFL D

Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET RECTANGLE OCULT 2x9 .Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, dø. LOW VOC and Low formaldehyde emissions. Luminaire model OD1RE918MF830DBB 3000K and CRI80. Electronic DALI gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.



Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 3.240 lm
 %:
 3000

 Plum:
 40W
 CRI:
 80

 Efficacy:
 81 lm/w
 MacAdam:
 3

 UGR:
 <10</td>
 Power Supply:
 220-240V 50/60Hz

 Type:
 HIGH POWER LED
 Gear:
 Adjustable DALI

LED Lifetime: 50.000 L90 B10 (Ta=25°C)

Power: 18W

Light output tolerance +/- 10%















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















QROD12936MF830D

QUIET RECTANGLE OCULT 2x9 3600 WW MFL D

PHOTOMETRIC DATA:

OD1RE918MF830NBB η = 100% lmax = 4606 cd/klm UTE: CIE: 102 100 100 100 100

CIE. 102 100 100 100 100

