
QROD12936WF840N



QUIET RECTANGLE OCULT 2x9 3600 NW WFL

Description:

LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET RECTANGLE OCULT 2x9 .Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, dø. LOW VOC and Low formaldehyde emissions. Luminaire model OD1RE918WF840NBB 4000K and CRI80. Electronic ON OFF gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.



Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 3.240 lm °K: 4000 Plum: 40W CRI: 80 Efficacy: 82,4 lm/w 3 MacAdam:

UGR: <16

Type: HIGH POWER LED Gear: Electronic

LED Lifetime: 50.000 L90 B10 (Ta=25°C)

18W Power:

Light output tolerance +/- 10%

















CUSTOM MADE OPTIONS:



















Power Supply:





120-277V 50/60Hz



QROD12936WF840N

QUIET RECTANGLE OCULT 2x9 3600 NW WFL

PHOTOMETRIC DATA:

OD1RE918WF840NBB η = 100% lmax = 1615 cd/klmUTE: CIE: 99 100 100 100 100

