


QSOD10918MF840N



QUIET SQ OCULT 9 1800 NW MFL

Description:


LAMP Luminaire integrated in a sound-absorbing structure made of rPET recycled material. Model QUIET SQ OCULT 9 1800 .Acoustic material: Panel thickness 12mm (Option 24mm), board composition: rPET 75% recycled. Fire resistance: B-s1, d0. LOW VOC and Low formaldehyde emissions. Luminaire model OD1RE918MF840NBB 4000K and CRI80. Electronic ON OFF gear included. IP43 rate. Insulation Class I. Photobiological safety group 0. LED life time: 50.000 L90 B10. Standard finishes: K05 Charcoal, Z04 Light Camel and Z97 Cactus Green. Further colours available on request.

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.620 lm	°K :	4000
Plum:	20W	CRI :	80
Efficacy:	81 lm/w	MacAdam:	3
UGR:	<10	Power Supply:	120-277V 50/60Hz
Type:	HIGH POWER LED	Gear:	Electronic
LED Lifetime:	50.000 L90 B10 (Ta=25°C)		
Power:	18W		

Light output tolerance +/- 10%




CUSTOM MADE OPTIONS:



QSOD10918MF840N

QUIET SQ OCULT 9 1800 NW MFL

PHOTOMETRIC DATA :



Essential Colours



Trendy Colours



Prime Colours

