Product datasheet

RING


RI140RD02SP927NB



RING 40 RD 150 VWW SP WH.

Description:

Fixed individual round downlight model RING 40 RD 150, LAMP brand. Made of aluminium. Model for HIGH POWER, 2700K color temperature and CRI 90. SPOT polycarbonate optics with high visual comfort thanks to the flush position of the lamp. IP43 protection rating. Insulation class I. With built-in electronic equipment (700mA). Lifetime: 100.000 L80 B10. Available finishes: Matt white (RAL 9010), Matt black (RAL 9011).



Finish: Matte black RAL 9011

Weight: 101 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 105 lm °K: 2700 Plum: 3,1W (700MA) CRI: 90 Efficacy: 33,9 lm/w 3 MacAdam:

Type: HIGH POWER LED Power Supply: 100-240V 50/60Hz

LED Lifetime: 100.000 L80 B10 (Ta=25°C) Gear: Electronic

2W Power:

Light output tolerance +/- 10%























+34937366800

Web www.lamp.es

RING









PHOTOMETRIC DATA:


RI140RD02SP927NB $\eta = 98\%$ $Imax = 25163 \ cd/klm$ UTE:


CIE: 108 100 100 100 98




















Data according to regulations 2019/2020/EU and 2019/2015/EU