Product datasheet

RING


RING THINNER FRAME RD 1300 WW MFL DIM WH

RI190RD10MF830TW



Description:

Fixed individual round downlight model RING THINNER FRAME RD 1300, LAMP brand. Made of white-lacquered aluminium. With a very thin frame. Model for COB LED, 3000K color temperature and CRI 80. Medium Flood highpurity faceted aluminium reflector. High visual comfort thanks to the non-flushed position of the lamp. IP43 protection rating. Insulation class II. Electronic equipment incorporated. Lifetime: 50.000 L70



Finish: Matte white RAL 9010

Weight: 264 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 971 lm °K: 3000 Plum: 11,8W CRI: 80 Efficacy: 82,3 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime: 50.000 L70 (Ta=25°C) Gear: Adjustable TRIAC

10W Power:

Light output tolerance +/- 10%























+34937366800


RING








PHOTOMETRIC DATA:





alpha = 28,2°	H (m)	D (m)	Emax	Emed
\bigwedge	1	0,50	3041	2096
	2	1,00	760	524
	3	1,51	338	233
	4	2,01	190	131

RING



