#### **Product datasheet**

#### **RING**

# LAMP Worktitude for light


#### **RI190SQ10MF830TW**



# RING THINNER FRAME SQ 1300 WW MFL DIM WH

#### Description:

Fixed individual square downlight model RING THINNER FRAME SQ 1300, LAMP brand. Made of white-lacquered aluminium. With a very thin frame. Model for COB LED, 3000K color temperature and CRI 80. Medium Flood high-purity faceted aluminium reflector. High visual comfort thanks to the non-flushed position of the lamp. IP43 protection rating. Insulation class II. Electronic equipment incorporated. Lifetime: 50.000 L70



Finish: Matte white RAL 9010

Weight: 264 g

Installation: Recessed

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 971 lm
 °K:
 3000

 Plum:
 11,8W
 CRI:
 80

 Efficacy:
 82,3 lm/w
 MacAdam:
 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L70 (Ta=25°C)
 Gear:
 Adjustable TRIAC

Power: 10W

#### Light output tolerance +/- 10%





















LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

+34937366800


### **RING**






### RING THINNER FRAME SQ 1300 WW MFL DIM WH

#### **PHOTOMETRIC DATA:**





alpha = 28,2°	H (m)	D (m)	Emax	Emed
$\wedge$	1	0,50	3041	2096
	2	1,00	760	524
	3	1,51	338	233
	4	2,01	190	131

# **RING**



