#### **Product datasheet**

#### **SHOT 180**

# **LAMP**Worktitude for light


#### **SH250SP840NA**



#### **SHOT 180 5000 SP 80 NW ANT**

#### Description:

Outdoor spotlight model SHOT 180 5000, LAMP brand. Made of lacquered aluminium injection and tempered glass, stainless steel screws and silicone joints. Model for LED HI-POWER, 4000K colour temperature, CRI 80 and control gear included. With Spot optics. IP65, IK05 protection rating. Insulation class I. Lifetime: 60. 000 L90B10. BUG Rate: B0 U0 G0, ULOR: 0%. Available finishes: anthracite and textured grey



Finish: Textured anthracite

Weight: 6.378 g

Maximum surface exposed to wind: 0.05 M2

Installation: Surface

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 4.127 lm
 °K:
 4000

 Plum:
 41W
 CRI:
 80

 Efficacy:
 100,7 lm/w
 MacAdam:
 3

Type: HIGH POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 37W

#### Light output tolerance +/- 10%

























## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU






















## **SHOT 180**




**SH250SP840NA** 

### SHOT 180 5000 SP 80 NW ANT

### PHOTOMETRIC DATA:





alpha = 11,1°	H (m)	D (m)	Emax	Emed
	1	0,19	59505	39549
	2	0,39	14876	9887
	3	0,58	6612	4394
	4	0,78	3719	2472

### **Product datasheet**

## **SHOT 180**



ACCESORIES:

Optical



Product code:

Description:

SHSC184B SHOT 180 ACC. ANTIGLARE SCREEN