#### **Product datasheet**

## **STORMBELL**

## LAMP Worktitude for light


## ST117030FL830NOB



## STORMBELL DECO 3000 WW FL BK.

## Description:

LAMP pendant luminaire model STORMBELL DECO 3000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP20, IK07 ratings. Insulation Class I. LED life time: 50.000 L80 B10. Available finishes: White and black.



Finish: Shiny black RAL 9011

Weight: 4.504 g

Installation: Suspended

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.648 lm
 % :
 3000

 Plum:
 26,3W
 CRI :
 80

 Efficacy:
 100,7 lm/w
 MacAdam:
 <3</td>

**Type:** COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 25W

## Light output tolerance +/- 10%















# CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU
















## **STORMBELL**




ST117030FL830NOB

## STORMBELL DECO 3000 WW FL BK.

## **PHOTOMETRIC DATA:**





alpha = 39,3°	H (m)	D (m)	Emax	Emed
	1	0,71	4632	3058
	2	1,43	1158	765
	3	2,14	515	340
	4	2,86	290	191

## **STORMBELL**



## ACCESORIES:

## Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR

Description:

STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

## Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

## Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

ae:

Description:

STORMBELL ACC. HONEYCOMB GRILLE