Product datasheet


STORMBELL

ST117030FL830NOW

STORMBELL DECO 3000 WW FL WH.

Description:

LAMP pendant luminaire model STORMBELL 3000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP20, IK07 ratings. Insulation Class I. LED life time: 50.000 L80 B10. Available finishes: White and black.



Finish: Shiny white RAL 9010

Weight: 4.504 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 2.648 lm °K: 3000 Plum: 26,3W CRI: 80 Efficacy: 100,7 lm/w MacAdam: <3

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

25W Power:

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU


















STORMBELL




ST117030FL830NOW

STORMBELL DECO 3000 WW FL WH.

PHOTOMETRIC DATA:





alpha = 39,3°	H (m)	D (m)	Emax	Emed
	1	0,71	4632	3058
	2	1,43	1158	765
	3	2,14	515	340
	4	2,86	290	191

STORMBELL



ACCESORIES:

Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR

Description:

STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

ae:

Description:

STORMBELL ACC. HONEYCOMB GRILLE