Product datasheet

STORMBELL


Worktitude for light

ST117030WF830NOB

STORMBELL DECO 3000 WW WFL BK.

Description:

LAMP pendant luminaire model STORMBELL 3000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP20, IK07 ratings. Insulation Class I. LED life time: 50.000 L80 B10. Available finishes: White and black.



Finish: Shiny black RAL 9011

Weight: 4.504 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 2.985 lm
 % :
 3000

 Plum:
 26,3W
 CRI :
 80

 Efficacy:
 113,5 lm/w
 MacAdam:
 <3</td>

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 25W

Light output tolerance +/- 10%



CLASE I









CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU


















STORMBELL





ST117030WF830NOB

STORMBELL DECO 3000 WW WFL BK.

PHOTOMETRIC DATA:







H (m)	D (m)	Emax	Emed
1	1,12	2370	1541
2	2,23	593	385
3	3,35	263	171
4	4,47	148	96

STORMBELL



ACCESORIES:

Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR

Description:

STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

Description:

STORMBELL ACC. HONEYCOMB GRILLE