Product datasheet

STORMBELL

Worktitude for light


ST117030WF840NOW



STORMBELL DECO 3000 NW WFL WH.

Description:

LAMP pendant luminaire model STORMBELL DECO 5000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector wide flood, with colour temperature 4000K and CRI80. Electronic ON OFF gear included. IP20, IK07 ratings. Insulation Class I. LED life time: 50.000 L80 B10. Available finishes: White and black.



Finish: Shiny white RAL 9010

Weight: 4.504 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 3.068 lm
 °K:
 4000

 Plum:
 26,3W
 CRI:
 80

 Efficacy:
 116,6 lm/w
 MacAdam:
 <3</td>

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 25W

Light output tolerance +/- 10%















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU















STORMBELL





99


ST117030WF840NOW

STORMBELL DECO 3000 NW WFL WH.

PHOTOMETRIC DATA:







STORMBELL



ACCESORIES:

Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR

Description:

STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

Description:

STORMBELL ACC. HONEYCOMB GRILLE