#### **Product datasheet**

## **STORMBELL**


## ST117050FL830NOB



## STORMBELL DECO 5000 WW FL BK.

## Description:

LAMP pendant luminaire model STORMBELL 5000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L80 B10. Available finishes: White and black.



Finish: Shiny black RAL 9011

Weight: 4.592 g

Installation: Suspended

## **TECHNICAL SPECIFICATIONS:**

Light output: 4.152 lm °K: 3000 Plum: 47,4W CRI: 80 Efficacy: 87,6 lm/w MacAdam: <3

Type: СОВ Power Supply: 100-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

44W Power:

## Light output tolerance +/- 10%















## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU


















# **STORMBELL**




ST117050FL830NOB

## STORMBELL DECO 5000 WW FL BK.

## **PHOTOMETRIC DATA:**





alpha = 39,3°	H (m)	D (m)	Emax	Emed
	1	0,71	7309	4825
	2	1,43	1827	1206
	3	2,14	812	536
	4	2,86	457	302

## **STORMBELL**



# ACCESORIES:

# Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR

Description:

STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

## Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

# Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

ae:

Description:

STORMBELL ACC. HONEYCOMB GRILLE