Product datasheet

STORMBELL

Worktitude for light


ST117050FL830NOW

III III

STORMBELL DECO 5000 WW FL WH.

Description:

LAMP pendant luminaire model STORMBELL DECO 5000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L80 B10. Available finishes: White and black.



Finish: Shiny white RAL 9010

Weight: 4.592 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 4.152 lm
 % : 3000

 Plum:
 47,4W
 CRI : 80

 Efficacy:
 87,6 lm/w
 MacAdam: <3</td>

Type: COB **Power Supply:** 100-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 44W

Light output tolerance +/- 10%















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU
















STORMBELL




ST117050FL830NOW

STORMBELL DECO 5000 WW FL WH.

PHOTOMETRIC DATA:





alpha = 39,3°	H (m)	D (m)	Emax	Emed
	1	0,71	7309	4825
	2	1,43	1827	1206
	3	2,14	812	536
	4	2,86	457	302

STORMBELL



ACCESORIES:

Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR

Description:

STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

ae:

Description:

STORMBELL ACC. HONEYCOMB GRILLE