#### **Product datasheet**

#### **STORMBELL**


#### ST117050FL840NBW

# 

#### STORMBELL 5000 NW FL WH.

#### Description:

LAMP pendant luminaire model STORMBELL 5000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 4000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L80 B10. Available finishes: White and black.



Finish: Shiny white RAL 9010

Weight: 4.592 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 3.793 lm °K: 4000 Plum: 47,4W CRI: 80 Efficacy: 80 lm/w MacAdam: <3

Type: СОВ Power Supply: 100-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

44W Power:

## Light output tolerance +/- 10%

















# **CUSTOM MADE OPTIONS:**
























# **STORMBELL**




ST117050FL840NBW

# STORMBELL 5000 NW FL WH.

## **PHOTOMETRIC DATA:**





alpha = 39,2°	H (m)	D (m)	Emax	Emed
	1	0,71	7541	4985
	2	1,42	1885	1246
	3	2,14	838	554
	4	2,85	471	312

# **STORMBELL**



# ACCESORIES:

# Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR



STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

# Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

Description:

STORMBELL ACC. HONEYCOMB GRILLE