Product datasheet

STORMBELL

ST117050FL840NOW



STORMBELL DECO 5000 NW FL WH.


Shiny white RAL 9010

Description:

Finish:

Weight: 4.592 g

LAMP pendant luminaire model STORMBELL DECO 5000 . Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 4000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L80 B10. Available finishes: White and black.



Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	4.267 lm	°K :	4000	
Plum:	47,4W	CRI :	80	
Efficacy:	90 lm/w	MacAdam:	<3	
Туре:	СОВ	Power Supply:	100-240V 50/60Hz	
LED Lifetime:	50.000 L80 B10 (Ta=25⁰C)	Gear:	Electronic	
Power:	44W			

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



Worktitude for light

STORMBELL

ST117050FL840NOW

STORMBELL DECO 5000 NW FL WH.



10440020	180°	alpha = 39,3°	H (m)	D (m)	Emax	Emed
$\eta = 100\%$			1	0,71	7512	4958
Imax = 1765 cd/klm UTE: 0,98A + 0,02T	90° 90°		2	1,43	1878	1240
CIE: 89 96 99 98 100			-	1,10	10/0	
			3	2,14	835	551
	02		4	2,86	470	310

Worktitude for light

Product datasheet

STORMBELL

ACCESORIES :

Optical




Product code: ST102OP

Description: STORMBELL ACC. OPAL GLASS



Product code: ST102TR



Worktitude for light



Product code: STBE420B





Description: STORMBELL ACC. BELL OPAL



Product code: STBE420W

Description: STORMBELL ACC. BELL WH.



Product code: STHO102B

Description: STORMBELL ACC. HONEYCOMB GRILLE