#### **Product datasheet**

#### **STORMBELL**

# Worktitude for light


## ST117050WF830NOB



#### STORMBELL DECO 5000 WW WFL BK.

#### Description:

LAMP pendant luminaire model STORMBELL 5000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L80 B10. Available finishes: White and black.



Finish: Shiny black RAL 9011

Weight: 4.592 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 4.707 lm
 ⁰K:
 3000

 Plum:
 47,4W
 CRI:
 80

 Efficacy:
 99,3 lm/w
 MacAdam:
 <3</td>

**Type:** COB **Power Supply:** 100-240V 50/60Hz

LED Lifetime: 50.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 44W

### Light output tolerance +/- 10%















## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU
















## **STORMBELL**





ST117050WF830NOB

## STORMBELL DECO 5000 WW WFL BK.

### **PHOTOMETRIC DATA:**







H (m)	D (m)	Emax	Emed
1	1,13	3743	2416
2	2,26	936	604
3	3,39	416	268
4	4,52	234	151

## **STORMBELL**



# ACCESORIES:

# Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR

Description:

STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

## Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

# Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

ae:

Description:

STORMBELL ACC. HONEYCOMB GRILLE