Product datasheet

STORMBELL

ST117050WF840NOB




STORMBELL DECO 5000 NW WFL BK.

Description:

Finish:

LAMP pendant luminaire model STORMBELL 8000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector wide flood, with colour temperature 4000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L90 B10. Available finishes: White and black.



Weight: 4.592 g

Shiny black RAL 9011

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	4.837 lm	⁰K :	4000		
Plum:	47,4W	CRI :	80		
Efficacy:	102 lm/w	MacAdam:	<3		
Туре:	СОВ	Power Supply:	100-240V 50/60Hz		
LED Lifetime:	50.000 L80 B10 (Ta=25°C)	Gear:	Electronic		
Power:	44W				

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light

STORMBELL

ST117050WF840NOB

STORMBELL DECO 5000 NW WFL BK.



10440032	180°	alpha = 58,9°	H (m)	D (m)	Emax	Emed
η = 100%			1	1,13	3846	2483
lmax = 797 cd/klm						ļ
UTE: 0,98B + 0,02T	90° 90°		2	2,26	962	621
CIE: 71 91 99 98 100						ļ
			3	3,39	427	276
	0°		4	4,52	240	155

Worktitude for light

Product datasheet

STORMBELL

ACCESORIES :

Optical




Product code: ST102OP

Description: STORMBELL ACC. OPAL GLASS



Product code: ST102TR



Worktitude for light



Product code: STBE420B





Description: STORMBELL ACC. BELL OPAL



Product code: STBE420W

Description: STORMBELL ACC. BELL WH.



Product code: STHO102B

Description: STORMBELL ACC. HONEYCOMB GRILLE