### **Product datasheet**

### **STORMBELL**

### ST117080FL830NBW



### STORMBELL 8000 WW FL WH

### Description:

LAMP pendant luminaire model STORMBELL DECO 8000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L90 B10. Available finishes: White and black.



Finish: Shiny white RAL 9010

Weight: 4.504 g

Installation: Suspended

### **TECHNICAL SPECIFICATIONS:**

Light output: 4.884 lm °K: 3000 Plum: 68W CRI: 80 Efficacy: 71,8 lm/w 2 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

60W Power:

### Light output tolerance +/- 10%



















# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU

















# **STORMBELL**




ST117080FL830NBW


# STORMBELL 8000 WW FL WH


### **PHOTOMETRIC DATA:**


ST117080FL830NBW  $\eta$  = 100% lmax = 2042 cd/klmUTE: 1,00A

CIE: 96 100 100 100 100









# **STORMBELL**



# ACCESORIES:

# Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR

Description:

STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

# Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

Description:

STORMBELL ACC. HONEYCOMB GRILLE