Product datasheet

STORMBELL

Worktitude for light


ST117080FL830NOB



STORMBELL DECO 8000 WW FL BK

Description:

LAMP pendant luminaire model STORMBELL 8000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L90 B10. Available finishes: White and black.



Finish: Shiny black RAL 9011

Weight: 4.504 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 5.517 lm
 % :
 3000

 Plum:
 68W
 CRI :
 80

 Efficacy:
 81,1 lm/w
 MacAdam:
 2

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 60W

Light output tolerance +/- 10%















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















STORMBELL




ST117080FL830NOB


STORMBELL DECO 8000 WW FL BK


PHOTOMETRIC DATA:


ST117080FL830NOB η = 100% Imax = 1906 cd/klm UTE: 1,00A

CIE: 93 99 100 100 100









STORMBELL



ACCESORIES:

Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR



STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

Description:

STORMBELL ACC. HONEYCOMB GRILLE