Product datasheet

STORMBELL




ST117080FL840NOB



STORMBELL DECO 8000 NW FL BK

Description:

LAMP pendant luminaire model STORMBELL 8000 . Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 4000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L90 B10. Available finishes: White and black.



Finish: Shiny black RAL 9011

Weight: 4.504 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 5.649 lm °K: 4000 Plum: 68W CRI: 80 Efficacy: 83,1 lm/w 2 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

60W Power:

Light output tolerance +/- 10%







CUSTOM MADE OPTIONS:

























STORMBELL




ST117080FL840NOB


STORMBELL DECO 8000 NW FL BK


PHOTOMETRIC DATA:


ST117080FL840NOB η = 100% Imax = 1906 cd/klm UTE: 1,00A

CIE: 93 99 100 100 100









STORMBELL



ACCESORIES:

Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR

Description:

STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

Description:

STORMBELL ACC. HONEYCOMB GRILLE