#### **Product datasheet**

#### **STORMBELL**


# Worktitude for light

#### ST117080FL840NOW

#### STORMBELL DECO 8000 NW FL WH

#### Description:

LAMP pendant luminaire model STORMBELL DECO 8000 . Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 4000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L90 B10. Available finishes: White and black.



Finish: Shiny white RAL 9010

Weight: 4.504 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 5.649 lm
 %:
 4000

 Plum:
 68W
 CRI:
 80

 Efficacy:
 83,1 lm/w
 MacAdam:
 2

**Type:** COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 60W

#### Light output tolerance +/- 10%















#### **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU

















#### **STORMBELL**



ST117080FL840NOW


#### STORMBELL DECO 8000 NW FL WH


## Worktitude for light


#### **PHOTOMETRIC DATA:**


ST117080FL840NOW  $\eta = 100\%$   $Imax = 1906 \ cd/kIm$   $UTE: \ 1,00A$ 

CIE: 93 99 100 100 100









#### **STORMBELL**



### ACCESORIES:

#### Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR



STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

#### Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

### Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

Description:

STORMBELL ACC. HONEYCOMB GRILLE