Product datasheet

STORMBELL

Worktitude for light


ST117080WF830NOW



STORMBELL DECO 8000 WW WFL WH

Description:

LAMP pendant luminaire model STORMBELL DECO 8000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector flood, with colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L90 B10. Available finishes: White and black.



Finish: Shiny white RAL 9010

Weight: 4.504 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 6.371 lm
 °K:
 3000

 Plum:
 68W
 CRI:
 80

 Efficacy:
 93,7 lm/w
 MacAdam:
 2

Type: COB **Power Supply:** 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

Power: 60W

Light output tolerance +/- 10%















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU















STORMBELL





ST117080WF830NOW


STORMBELL DECO 8000 WW WFL WH

PHOTOMETRIC DATA:

ST117080WF830NOW η = 100% lmax = 941 cd/klmUTE: 1,00B CIE: 80 96 99 100 100







STORMBELL



ACCESORIES:

Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR



STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

Description:

STORMBELL ACC. HONEYCOMB GRILLE