#### **Product datasheet**

#### **STORMBELL**


## ST117080WF840NBW



#### STORMBELL 8000 NW WFL WH

#### Description:

LAMP pendant luminaire model STORMBELL DECO 8000. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector wide flood, with colour temperature 4000K and CRI80. Electronic ON OFF gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L90 B10. Available finishes: White and black.



Finish: Shiny white RAL 9010

Weight: 4.504 g

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 5.271 lm °K: 4000 Plum: 68W CRI: 80 Efficacy: 77,5 lm/w 2 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

60W Power:

### Light output tolerance +/- 10%





















## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU

















## **STORMBELL**




ST117080WF840NBW


## STORMBELL 8000 NW WFL WH


### **PHOTOMETRIC DATA:**

ST117080WF840NBW  $\eta = 100\%$ Imax = 976 cd/klm UTE: 1,00B

CIE: 79 96 100 100 100







## **STORMBELL**



# ACCESORIES:

## Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR



STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

## Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

# Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

Description:

STORMBELL ACC. HONEYCOMB GRILLE