Product datasheet

STORMBELL


ST117080WF840NOW



STORMBELL DECO 8000 NW WFL WH

Description:

LAMP pendant luminaire model STORMBELL DECO 8000 NW WFL. Body made of extruded and die-cast aluminium. COB model with polycarbonate reflector wide flood, with colour temperature 4000K and CRI80. Electronic DALI gear included. IP20, rating. Insulation Class I. LED life time: 50.000 L80 B10. Available finishes: White and black.



Finish: Shiny white RAL 9010

Weight: 4.504 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 6.524 lm °K: 4000 Plum: 68W CRI: 80 Efficacy: 95,9 lm/w 2 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

60W Power:

Light output tolerance +/- 10%















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















STORMBELL





ST117080WF840NOW


STORMBELL DECO 8000 NW WFL WH

PHOTOMETRIC DATA:

ST117080WF840NOW
η = 100%
Imax = 941 cd/klm
UTE: 1,00B
CIE: 80 96 99 100 100







STORMBELL



ACCESORIES:

Optical



Product code:

ST102OP



STORMBELL ACC. OPAL GLASS



Product code:

ST102TR



STORMBELL ACC. TRANS GLASS



Product code:

STBE420B

Description:

STORMBELL ACC. BELL BK.



Product code:

STBE420OP

Description:

STORMBELL ACC. BELL OPAL



Product code:

STBE420W

Description:

STORMBELL ACC. BELL WH.



Product code:

STHO102B

Description:

STORMBELL ACC. HONEYCOMB GRILLE