


ST18SELOWF940DOPB



STORMBELL 80 DECO SU RE 1500 NW WF D O/B

Description:

Downlight to suspend model STORMBELL 80 DECO SU RE 1500 NW WFL DA OP/BK LAMP brand. Body made of injected aluminum with white/black/Materiality finish, and with black/opal polycarbonate ring, for decorative lighting effect and possibility of accessory color filter, depending on his model. COB LED 4000K color temperature and CRI90. Aluminium reflector WIDE FLOOD. Luminaire with ceiling rose and electronic DALI equipment included. Insulation class II. LED life time: 50000 L90 B10. Compatible with 4 different models of bells (accessories) that complete the luminaire.

Finish: Texturised black RAL 9011

Weight: 800 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.460 lm	°K :	4000
Plum:	14,5W	CRI :	90
Efficacy:	100,7 lm/w	R9 :	65
Type:	COB	MacAdam:	3
LED Lifetime:	50.000 L90 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	12.2W	Gear:	Adjustable DALI


Light output tolerance +/- 10%

**CUSTOM MADE OPTIONS:**

ST18SELOWF940DOPB

STORMBELL 80 DECO SU RE 1500 NW WF D O/B

PHOTOMETRIC DATA :



ACCESSORIES :
Optical

Product code:

HSHO50

Description:

HANCE 1000/2000 ACC. HONEYCOMB GRILLE


Product code:

S8BE227B

Description:

ACC. BELL STORMBELL 80 Ø227x89 BK


Product code:

S8BE227B1

Description:

ACC. BELL STORMBELL 80 Ø227x89 MA


Product code:

S8BE227W

Description:

ACC. BELL STORMBELL 80 Ø227x89 WH


Product code:

S8BE363B

Description:

ACC. BELL STORMBELL 80 Ø363x60 BK


Product code:

S8BE363B1

Description:

ACC. BELL STORMBELL 80 Ø363x60 MA


Product code:

S8BE363CK

Description:

ACC. BELL STORMBELL 80 Ø363x60 CK


Product code:

S8BE363PT

Description:

ACC. BELL STORMBELL 80 Ø363x60 PT


Product code:

S8BE363W

Description:

ACC. BELL STORMBELL 80 Ø363x60 WH


Product code:

S8BE86B

Description:

ACC. BELL STORMBELL 80 Ø86x50 BK



Product code:
S8BE86B1

Description:
ACC. BELL STORMBELL 80 Ø86x50 MA



Product code:
S8BE86W

Description:
ACC. BELL STORMBELL 80 Ø86x50 WH