#### **Product datasheet**

# **TRACE 65**

### TC120V0265SY830NB



### TRACE IP65 200 VERT 120 WW BK.

#### **Description:**

Finish:

Outdoor wall-recessed luminaire model TRACE IP65 200 VERT 120 LAMP brand. Body made of injected aluminium and matt black serigraphed tempered glass. Model for MID-POWER LED with 3000K, CRI 80 colour temperature and control gear included. Texturised white lacquered aluminium symmetric reflector. IP65, IK07 protection rating. Insulation class I. Lifetime: 100. 000 L90 B10. BUG Rate: B0 U2 G1, ULOR: 42%.



Dimensions: 115 x 214 x 145 mm

CATAPHORESIS

Weight: 1.204 g

Installation: Wall recessed

Recessing measures: 107 x 212 x 135 mm

### **TECHNICAL SPECIFICATIONS:**

Light output:	156 lm	°K :	3000
Plum:	4,1W	CRI :	80
Efficacy:	38 lm/w	MacAdam:	<3
Туре:	MID POWER LED	Power Supply:	100-240V 50/60Hz
LED Lifetime:	100.000 L90 B10 (Ta=25°C)	Gear:	Electronic
Power:	3W		

### Light output tolerance +/- 10%



### CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light

## **TRACE 65**

TC120V0265SY830NB

TRACE IP65 200 VERT 120 WW BK.



### **PHOTOMETRIC DATA :**

5641532	180°	alpha = 600,0°	H (m)	D (m)	Emax	Emed
$\eta = 100\%$			1	0,00	-1	NAN
Imax = 354 cd/klm UTE: 0,50T	90° 90°		2	0,00	0	NAN
CIE: 11 36 67 50 100			-			
			3	0,00	0	NAN
	0°		4	0,00	0	NAN

### Product datasheet

# **TRACE 65**

## ACCESORIES :

Assembly



Product code: TCREBO65200 Description: TRACE IP65 ACC. 200 REC BOX

LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Worktitude for light