#### **Product datasheet**

#### **TRACE 65**

#### TC120V0265SY830NB

#### **TRACE IP65 200 VERT 120 WW BK.**

#### Description:

Outdoor wall-recessed luminaire model TRACE IP65 200 VERT 120 LAMP brand. Body made of injected aluminium and matt black serigraphed tempered glass. Model for MID-POWER LED with 3000K, CRI 80 colour temperature and control gear included. Texturised white lacquered aluminium symmetric reflector. IP65, IK07 protection rating. Insulation class I. Lifetime: 100. 000 L90 B10. BUG Rate: B0 Ú2 G1, ULOR: 42%.



Finish: **CATAPHORESIS** 

115 x 214 x 145 mm Dimensions: Weight: 1.204 g

Installation: Wall recessed

107 x 212 x 135 mm Recessing measures:

#### **TECHNICAL SPECIFICATIONS:**

Light output: 156 lm °K: 3000 Plum: 4,1W CRI: 80 Efficacy: 38 lm/w MacAdam: <3

Type: MID POWER LED Power Supply: 100-240V 50/60Hz

LED Lifetime: 100.000 L90 B10 (Ta=25°C) Gear: Electronic

3W Power:

#### Light output tolerance +/- 10%



















#### **CUSTOM MADE OPTIONS:**














# **TRACE 65**




TC120V0265SY830NB

## **TRACE IP65 200 VERT 120 WW BK.**

## PHOTOMETRIC DATA:





alpha = 600,0°	H (m)	D (m)	Emax	Emed
	1	0,00	-1	NAN
	2	0,00	0	NAN
	3	0,00	0	NAN
	4	0,00	0	NAN

## **Product datasheet**

# **TRACE 65**



ACCESORIES:

Assembly



Product code: Description:

TCREBO65200 TRACE IP65 ACC. 200 REC BOX